

Premium Antiscalant and Antifoulant for Membrane Systems

Description

Flocon 260 is an aqueous solution of a specialised polycarboxylic acid, highly effective in controlling the deposition of inorganic scale forming salts and particulate fouling on membrane surfaces.

- Excellent control of carbonate scales, sulphate and fluoride for cost effective operation
- Effectively control both soluble and insoluble iron
- Effective against silica fouling
- Dispersant
- Compatible with all major membranes
- International potable water approvals

Application

Flocon 260 is an aqueous solution of an organic acid and as such is corrosive in its concentrated form. Corrosion resistant dosing equipment should therefore be used. Examples of suitable materials are 316L stainless steel, or plastics such as GRP, PVC and PE.

The recommended injection point is into the feedwater downstream of any filtration equipment and cartridge filters.

BATH NO: RM-S-2015011520

LOT NO:2021418

DOM. 07/2021

DOE. 07/2024

Usage

Flocon 260 is miscible with water in all proportions. It may be applied as the neat product, or as a solution in permeate. Minimum dosing solution strength of 10% w/w is recommended. Flocon 260 should be dosed continuously and proportionately to the feed water flow, to maintain the recommended dose level.

The dose level required is dependent on the quality of the feedwater and the saturation indices of the various scales forming species present in the concentrated brine. Proprietary computer software is used to calculate scaling indices and calculate optimum system recovery. Dose level projections and recommendations are available on request.

*Please consult with your BWA Water Additives representative to determine optimal dosage recommendations for your system.

Packaging / Weight

Pail	55 lb	25 kg
Drum	500 lb	230 kg
IBCs/Totes	2,204 lb	1,000 kg

*Consult your sales representative for availability.

Physical Properties

Appearance	Pale yellow liquid
pH	< 2
Specific gravity at 20/20°C	1.05 to 1.1
Freezing point range	0 to -10 °C

Further details are available in the safety data sheet



Americas

1979 Lakeside Parkway,
Suite 925
Tucker, GA 30084, USA
Phone +1 678 802 3050
Or 800 600 4523
Fax +1 678 802 3024
Americas@wateradditives.com

Asia Pacific

No. 1 Magazine Road
#04-01, Central Mall Office Tower
Singapore 059567
Phone +65 9745 3227
Fax +65 6234 3606
AsiaPacific@wateradditives.com

Europe

2 Brightgate Way
Stratford, Manchester M32 0TB
United Kingdom
Phone +44 161 864 6699
Fax +44 161 864 6666
Europe@wateradditives.com

MENA

DMCC Dubai Branch
Office 1802, Level 18
Jumeirah Bay X3 Tower, Cluster X
Jumeirah Lake Towers
P.O. Box 263164, Dubai, UAE
Phone +971 4 880 7336
Fax +971 4 880 7404
MiddleEast@wateradditives.com

Patents:

BWA Water Additives (BWA) owns or is the licensee of patents and patent applications, which may cover the products and/or uses described in this brochure.

The following are registered trademarks of BWA Belclene, Belcor, Belgard, Belite, Bellacide, Bellasol, Beisperse, BromsCide, Flocon, Geogard and Liquebrom Drop and Swirl logo. ® Registered US Patent and Trademark Office. © 2016 BWA all rights reserved.

The information contained in this product sheet is based on data available to BWA Water Additives at the time of publication. While BWA has made every effort to ensure this information is correct, no responsibility can be accepted by BWA for any loss or liability occasioned by any person acting or refraining from acting as a result of the contents of this publication. BWA cannot guarantee that the results described in this information will be achieved by others if BWA has not participated in the testing process. BWA therefore makes no warranty of merchantability or fitness for a particular purpose or any express or implied warranty in respect of this information. This information is intended for use by technically trained personnel at their discretion and risk and is not a substitute for specific professional or technical advice. BWA's liability shall be limited by its standard limitations of liability contained within its standard terms and conditions of sale if BWA makes any sales to you.

© 2016 all rights reserved. No part of this publication may be reproduced or transmitted in any form or by any means or stored in any retrieval system without the prior written permission of BWA Water Additives UK Limited. BWA Water Additives UK Limited is a private limited company registered in England and Wales at 2 Brightgate Way, Manchester M32 0TB, Registered No. 5657343.